

Heavy Duty Brake Fluid Chart

Brand	DOT Rating	Dry Boiling	Wet Boiling	Other fluid compatibility
AP Racing 550	DOT 3	550°F (287°C)	284°F (140°C)	Yes
AP Racing 600	DOT 3	572°F (300°C)	284°F (140°C)	No
ATE Super Blue	DOT 4	536°F (280°C)	382°F (194°C)	Yes
ATE Super 200 (amber color) (aka Type 200)	DOT 4	536°F (280°C)	382°F (194°C)	Yes
Bosch DOT 3	DOT 3	491°F (255°C)	288°F (142°C)	Yes
Bosch DOT 4	DOT 4	509°F (265°C)	329°F (165°C)	Yes
Bosch DOT 4+	DOT 4	536°F (280°C)	356°F (180°C)	Yes
Brembo LCF 600+	DOT 4	601°F (316°C)	399°F (204°C)	Yes
Castrol LMA	DOT 4	446°F (230°C)	311°F (155°C)	Yes
Castrol SRF	DOT 4	590°F (310°C)	518°F (270°C)	Yes
Ford HD (C6AZ-19542-AB)	DOT 3	550°F (287°C)	284°F (140°C)	Yes
GS 610	DOT 4	610°F (321°C)	421°F (216°C)	Yes
Motul DOT 5.1	DOT 5.1	509°F (265°C)	365°F (185°C)	Yes
Motul Racing Brake Fluid 600 (new)	DOT 4	594°F (312°C)	421°F (216°C)	Yes
Performance Friction Z-Rated	DOT 3	550°F (287°C)	284°F (140°C)	Yes
Valvoline ProSyn	DOT 3/4	502°F (261°C)	343°F (173°C)	Yes
Wilwood 570	DOT 3	570°F (299°C)	284°F (140°C)	Yes
Wilwood EXP600 Plus (new)	DOT 4	633°F (330°C)	417°F (213°C)	check w/manuf.

Minimum specifications for DOT Rating:	Dry Boiling	Wet Boiling
DOT 3	401°F	284°F
DOT 4	446°F	311°F
DOT 5	500°F	356°F